1. INFLUENCE OF THE PROTON CONCENTRATION ON THE PROPERTIES OF THE LiNbO₃ and LiTaO₃ CRYSTALS

Interim report 2

by

M.P. DE MICHELI

September 1996

United States Army

EUROPEAN RESEARCH OFFICE OF THE U.S. ARMY London England

CONTRACT NUMBER: N68171-96-C-9040

R&D 7774-EE-01

DTIC QUALITY INSPECTED 3

Laboratoire de Physique de la Matière Condensée
CNRS
Parc VALROSE, 06108 NICE CEDEX2, FRANCE

Approved for Public Release; distribution unlimited.

Fabrication of Proton exchanged waveguides

Since June, we have started to prepare PE waveguides with different recipes, in order to get waveguides presenting the different crystallographic phases identified in LiNbO₃. Those samples have been characterized optically, and we have been facing the problem of a rather poor reproducibility. On step index waveguides we measured up to 10% fluctuation on the index increase of samples prepared with the same recipe. For the samples presenting graded index profiles, the situation was even worse, as it was not always possible to avoid the formation of a surface layer presenting a high index increase and a step profile.

After different investigation, we have been able to demonstrate that these fluctuations were due to a non controlled amount of water incorporated in the benzoic acid -lithium benzoate mixture we use as a proton source. Improving this control allowed us to reduce the fluctuations of the index increase in the case of the step index profiles down to 1%. We are now building a suitable equipment to achieve a good control of the water amount in the melt, and of course this has slightly delayed the preparation of the samples.

Influence of the Proton exchanged process on the nonlinearity

Despite the reproducibility problems, some preliminary experiment aiming at measuring the nonlinear coefficient of different exchanged layers have been performed. They have shown dramatic differences depending on the recipe. In order to conclude more precisely, the spatial resolution of the nonlinear experiment has to be improved (this is currently done) and the samples have to be tested by X-rays and SIMS.

Influence of the Proton exchanged process on the poling

In this field also, preliminary experiment have demonstrated a great potential. Indeed, doing some proton exchange allows to significantly modify the poling field of the crystal. This has been demonstrated for large areas on the substrate. In order to be able to use this property to pattern the poling, we have now to study in more details the spatial behavior of the domains in PE exchanged substrates.

REPOR	RT DOCUMENTATION	PAGE	
1. AGENCY USE ONLY	2. REPORT DATE 09/30/96	3. REPORT TYPE AND DATE July - September 96	S COVERED
4. TITLE: Influence of the proton concentration on the properties of the LiNbO ₃ and LiTaO ₃ crystals 6. AUTHOR: M.P. DE MICHELI			5. FUNDING NUMBERS
7. PERFORMING ORGANIATION NAMES AND ADDRESSES Laboratories de Physique de la Matière Condensée, Parc Valrose, 06108 NICE Cedex 2, FRANCE			8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING, MONITORING AGENCY NAMES AND ADDRESSES			10. SPONSORING, MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTE	SS .		
12A. DISTRIBUTION / AVAILABILITY STATEMENT Approved for Public Release; distribution unlimited.			12B. DISTRIBUTION CODE
reproducibility (up to 19 were able to demonstrate the melt we used for the Preliminary experiment	reguides with the same re 0% fluctuation of the indi- te that this phenomenon e exchange. Thave been performed to tal and on its poling behavior	lex increase for step inde was due to an uncontrolled test the influence of the	x waveguides). We ed amount of water in Proton Exchange on the
14. SUBJECT TERMS			15. NUMBER OF PAGES
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF THE REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT